

DRX3

Refrigerant Leak Detector

Find Leaks Fast

Travel light with one tool, one sensor, that quickly and accurately detects HC, HFC, CFC, HFO, H2/N2 (tracer gas) and blend refrigerants, as well as natural gas, propane, butane, and methane combustible gases.

The DRX3 is designed for performance and safety, complying with ATEX Zone 2 and Class I, Division 2 hazardous location requirements.

Features

- Detects A3, A2L, A1 refrigerants, and combustible gases
- Flexible wand to reach tight spaces
- Multiple visual and audio leak indicators that change with leak intensity
- High, medium and low sensitivity settings
- Auto and manual zero modes
- Long-life, field-replaceable batteries
- Field-replaceable, heated diode sensor

Specifications

JobLink  A3|A2L

Sensor Type	Heated Diode
Sensor Life	300 Hours Typical
Max Sensitivity	0.03 oz/yr (1 g/yr)
Wireless Connection	Job Link® System App
Wireless Range	Up to 656' (200 m) Line of Sight
Battery Type	4x Replaceable AA Lithium Iron Disulfide (For ATEX and CID2 Compliance, Use 4x Energizer L91 AA Batteries)
Battery Life	60 Hours Typical
Display	LCD with Backlight
Weight	15.6 oz (442 g) w/ batteries
Dust / Water Resistance	IP54 Main Body
Detection Feedback	Flashing LED, LCD Bar Graph and Numerical Values, Audible Beep, Job Link® System App
Detects	Common A3 (R290, R600a, R600, R50, R1270), A2L (R32, R454B, R1234yf), and A1 refrigerants; H2/N2 Tracer Gas; Natural Gas, Methane, Propane, and Butane Combustible Gases
Not For Use With	R702, R717, R744
Compliance	ATEX Zone 2; Class I, Division 2 Hazardous Locations
Limited Warranty	1 year

©Fieldpiece Instruments, Inc. 2026, v02

