



VC1 | VC1G | VC2G

Valve Core Removal Tools

Faster Recovery, Verified.

Take control with faster refrigerant flow using one of three valve core removal tools designed to help HVACR technicians recover, evacuate and charge systems faster and with confidence, every time.

Features

- Locks in the valve core on the first try
- Sight glass to verify captured valve core and see refrigerant flow (VC1G, VC2G)
- Comfort spinner – a free-spinning, rubberized magnetic cap for easy removal and insertion against pressure (VC1G, VC2G)
- Second ball valve to protect connected vacuum gauge (VC2G)
- Compact size for tight space access (VC1)
- Swappable service port fitting (1/4" standard, 5/16" optional)
- Vacuum-rated to 20 microns

Specifications



	VC1	VC1G	VC2G
Valve Core	●	●	●
Capture Gasket	●	●	●
Magnetic Cap	●	●	●
Comfort Spinner		●	●
Sight Glass		●	●
Dual Ball Valves			●
Dimensions	4.3" x 1.6" x 1.5" (108 x 40 x 38 mm)	5.1" x 2" x 1.5" (129 x 51 x 38 mm)	5.1" x 2.6" x 1.5" (129 x 69 x 38 mm)
Weight	0.60 lbs (272 g)	0.71 lbs (322 g)	0.82 lbs (372 g)
Fitting	1/4" Female Service Port (5/16" optional) 1/4" Male Side Port with Removable Valve Core		
Maximum Working Pressure	800 psi / 55 Bar		
Vacuum Rating	20 microns / 0.027 millibar / 0.020 Torr		
Maximum Working Pressure	800 psi / 55 Bar		
Limited Warranty	1 year		
Patents	www.fieldpiece.com/patents		

©Fieldpiece Instruments, Inc. 2026, v02