

Fieldpiece



VP833

A3-Compatible Vacuum Pump

Travel Light with one pump.

Compatible with common A3, A2L and A1 refrigerants, the VP833 future-proofs your tool kit with the most versatile, ultra-fast 8 CFM vacuum pump.

Clearly see oil condition, fill level, and pump status in the large backlit window on the oil reservoir. With the RunQuick® Oil Change System, replace oil in under 20 seconds without losing vacuum, even while the pump is running. And the extra wide base helps prevent tipping and oil spills.

Features

- Class I, Division 2 hazardous location certified for safe use with A3 flammable refrigerants
- Change oil in 20 seconds without losing vacuum
- Wide mouth oil fill port
- 3/4 HP DC motor handles voltage fluctuations
- 4 in-line ports for easy hose access and connection
- Rated for 15 microns ultimate vacuum
- Gas ballast valve switch
- Rugged and lightweight for easy carry and transport

Specifications

A3|A2L

Flow Rate	8 CFM
Port Sizes	(1) 1/4", (2) 3/8", (1) 1/2"
For Use With	Common A3, A2L, and A1 Refrigerants
Not For Use With	R-702, R-717 Refrigerants
Safety Certification	Class I, Division 2, Groups A, B, C and D T4 23°F (-5°C) ≤ T _{AMB} ≤ 122°F (50°C)
Ultimate Vacuum	15 Microns
Compressor	Rotary Vane, Two Stage
Motor	3/4 HP Brushless DC, 2500 RPM
Dimensions	7.9" x 11.7" x 16.0" (201 mm x 296 mm x 406 mm)
Weight Empty	29 lb / 13 kg
Operating Temperature	23°F to 122°F (-5°C to 50°C)
Oil Capacity	8 oz Reservoir, Onboard Storage of (2) 8oz Containers
Status Indicators	Blue, Yellow, Red LEDs
Limited Warranty	1 Year
Patents	www.fieldpiece.com/patents

©Fieldpiece Instruments, Inc. 2026, v02